




## TK862

### Împrimantă de birou pentru bilete

TK862 este imprimanta de bilete compactă, flexibilă și robustă top de gamă. Datorită ghidajelor de hârtie reglabile (lățimea biletului de 40 la 86 mm) și alimentatorului dublu, TK862 este extrem de versatilă, permițând o reducere considerabilă a costurilor. Versiunea cu alimentator dublu vă permite să gestionați 2 tipuri diferite de hârtie. Cu versiunea Veriprint, un sistem patentat Custom, este posibilă verificarea instantanee a lizibilității datelor (de ex. codul de bare) în timpul fazei de tipărire a biletului și astfel evitarea emiterii de bilete cu valabilitate dubioasă. TK862 poate fi echipată cu antene originale CUSTOM HF/UHF RFID, un senzor CIS exclusiv, cu care să citească orice tip de bilet/etichetă și să asigure alinierea la tăietură. Ideal pentru soluții tradiționale de ticketing și fără contact.



## CARACTERISTICI

- Setare deosebit de simplă
- Este posibilă administrarea ultimului bilet
- Cap de imprimare: cu funcție de autodiagnostic
- Alimentare cu hârtie complet automată
- CIS pentru detectare Notch/Gap
- Controlul stocului non-termic (prin licență de activare)
- Citire/scriere etichetă RFID UHF (versiune IDU)
- Arhivarea/citirea imaginii tipărite (versiunea Veriprint)

## VERSIUNI SPECIALE

- **ALIMENTATOR DUBLU** cu lămpă hârtie reglabilă
- **VERIPRINT**
- **HF RFID**

---

## ACCESORII

- Suport hârtie pliată etichete la ieșire
- Licență de activare a controlului stocului de coduri de bare
- Suport de role
- **UHF RFID:** UHF EPC Gen2
- **HF CUSTOM RFID:** Mifare UltraLight, Mifare 1K\4K, Mifare UltraLight EV1, Mifare UltraLight C, Mifare UltraLight C + SAM, Mifare DESFire, Mifare Plus, NTAG 203 (NFC), NTAG 213 (NFC), Sri-Srx-Srt, Calypso, iCode SLI, iCode Texas

Inclus în pachet:

- Sursă de alimentare 24V - 100W, cablu USB de 1,8 m

## FI?? TEHNIC?

|                       |                                                                                                                                                                                                                                |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Printing Method       | Thermal with fixed head                                                                                                                                                                                                        |
| Number of dots        | 8 dots/mm                                                                                                                                                                                                                      |
| Resolution            | 203 dpi                                                                                                                                                                                                                        |
| Printing (mm/sec)     | 220 mm/sec (high speed)                                                                                                                                                                                                        |
| Supported Barcode     | 1D and 2D barcodes supported: UPC-A, UPC-E, EAN13, EAN8, CODE39, ITF, CODABAR, CODE93, CODE128, CODE32, PDF417, DATAMATRIX, AZTEC, QRCODE, GS1 Databar                                                                         |
| Printing Format       | Height/Width from 1 to 8, bold, reverse, underlined, italic                                                                                                                                                                    |
| Printing Direction    | Normal, 90°, 180°, 270°                                                                                                                                                                                                        |
| Paper width           | from 40 mm to 86 mm                                                                                                                                                                                                            |
| Paper weight          | from 70 to 255 g/m <sup>2</sup> (Dual feeder from 100 to 255 g/m <sup>2</sup> )                                                                                                                                                |
| Paper thickness       | max 280 μm                                                                                                                                                                                                                     |
| Roll Dimension        | max 300 mm (dual feeder max 150 mm)                                                                                                                                                                                            |
| Sensors               | Head temperature, paper presence, paper presence on output, front and upper cover open, top and front cover open, dual feeder paper input (only dual feeder models), CIS reader, CIS thermic side (only for Veriprint version) |
| Emulation             | CUSTOM/POS, SVELTA                                                                                                                                                                                                             |
| Interfaces            | RS232 / USB / Ethernet                                                                                                                                                                                                         |
| Flash Memory          | 2 MB internal + 8 MB external                                                                                                                                                                                                  |
| RAM Memory            | 640 KB internal + 8 MB external                                                                                                                                                                                                |
| Drivers               | Windows® (32/64 bit) – only on request WHQL and silent installation;<br>CUPS Linux (32/64 bit);<br>Virtual COM (Linux or Windows 32/64 bit);<br>Android™                                                                       |
| Software Tools        | PrinterSet, CustomPowerTool, Status Monitor                                                                                                                                                                                    |
| Power supply          | 24 Vdc ± 10%                                                                                                                                                                                                                   |
| Medium consumption    | 1.46 A (12,5% dots turned on)                                                                                                                                                                                                  |
| Head Life             | 100Km / 100M pulses                                                                                                                                                                                                            |
| MCBF (total cut)      | 1.500.000 cuts                                                                                                                                                                                                                 |
| Operating temperature | 0°C + 40°C                                                                                                                                                                                                                     |
| Dimensions            | 216(L) x 173(H) x 170(W) mm (standard model)<br>223(L) x 173(H) x 170(W) mm (model with ejector)<br>246(L) x 173(H) x 170(W) mm (model with dual feeder)                                                                       |
| Weight                | 4,85 Kg (standard model)<br>5 Kg (model with ejector)<br>6,1 Kg (model with dual feeder)                                                                                                                                       |

## MODELE



**911LU010100733**

PRINTER TK862 ETH USB RS232



**911LU011200733**

PRINTER TK862 ETH USB RS232  
RFID HF



**911LU010300733**

PRINTER TK862 ETH USB RS232  
EJECTOR



**911LU010200733**

PRINTER TK862 ETH USB RS232  
DF



**911LU020100733**

PRINTER TK862 ETH USB RS232  
VERIPRINT



**911LU020200733**

PRINTER TK862 ETH USB RS232  
VERIPRINT DF

---

Via Berettine, 2 - 43010 Fontevivo PR - TVA: IT02498250345 - TEL: +39 0521 680111 - FAX: +39 0521 610701 - COD UNIC: 8RQN7AZ

Datele tehnice de pe acest site nu sunt obligatorii și pot fi modificate fără nicio notificare.

Ultima actualizare: 17 mai 2024